



# N-channel 1500 V, 700 mΩ typ., 14 A MDmesh K5 Power MOSFET in a TO-247 package


**TO-247**


AM01476v1\_tab



## Features

Order code	$V_{DS}$	$R_{DS(on)}$ max.	$I_D$
STW21N150K5	1500 V	900 mΩ	14 A

- Ultra-low gate charge
- Very low FoM (figure of merit)
- Zener-protected
- 100% avalanche tested

## Applications

- Switching applications

## Description

This very high voltage N-channel Power MOSFET is designed using MDmesh K5 technology based on an innovative proprietary vertical structure. The result is a dramatic reduction in on-resistance and ultra-low gate charge for applications requiring superior power density and high efficiency.

### Product status link

[STW21N150K5](#)

### Product summary

Order code	STW21N150K5
Marking	21N150K5
Package	TO-247
Packing	Tube

# 1 Electrical ratings

**Table 1. Absolute maximum ratings**

Symbol	Parameter	Value	Unit
$V_{GS}$	Gate-source voltage	$\pm 30$	V
$I_D$	Drain current (continuous) at $T_C = 25\text{ }^{\circ}\text{C}$	14	A
	Drain current (continuous) at $T_C = 100\text{ }^{\circ}\text{C}$	8.7	
$I_{DM}^{(1)}$	Drain current (pulsed)	56	A
$P_{TOT}$	Total power dissipation at $T_C = 25\text{ }^{\circ}\text{C}$	446	W
$dv/dt^{(2)}$	Peak diode recovery voltage slope	4.5	V/ns
$dv/dt^{(3)}$	MOSFET $dv/dt$ ruggedness	50	V/ns
$T_{stg}$	Storage temperature range	-55 to 150	$^{\circ}\text{C}$
$T_J$	Operating junction temperature range		$^{\circ}\text{C}$

1. Pulse width is limited by safe operating area.
2.  $I_{SD} \leq 14\text{ A}$ ,  $di/dt = 100\text{ A}/\mu\text{s}$ ,  $V_{DS}(\text{peak}) < V_{(BR)DSS}$ .
3.  $V_{DD} \leq 1200\text{ V}$ .

**Table 2. Thermal data**

Symbol	Parameter	Value	Unit
$R_{thJC}$	Thermal resistance, junction-to-case	0.28	$^{\circ}\text{C}/\text{W}$
$R_{thJA}$	Thermal resistance, junction-to-ambient	50	$^{\circ}\text{C}/\text{W}$

**Table 3. Avalanche characteristics**

Symbol	Parameter	Value	Unit
$I_{AR}$	Avalanche current, repetitive or non-repetitive (pulse width limited by $T_J$ max.)	5	A
$E_{AS}$	Single pulse avalanche energy (starting $T_J = 25\text{ }^{\circ}\text{C}$ , $I_D = I_{AR}$ , $V_{DD} = 50\text{ V}$ )	1.1	J

## 2 Electrical characteristics

$T_C = 25\text{ °C}$  unless otherwise specified.

**Table 4. Static**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	$V_{GS} = 0\text{ V}$ , $I_D = 1\text{ mA}$	1500	-	-	V
$I_{DSS}$	Zero gate voltage drain current	$V_{GS} = 0\text{ V}$ , $V_{DS} = 1500\text{ V}$	-	-	1	$\mu\text{A}$
		$V_{GS} = 0\text{ V}$ , $V_{DS} = 1500\text{ V}$ , $T_C = 125\text{ °C}^{(1)}$	-	-	50	
$I_{GSS}$	Gate-body leakage current	$V_{DS} = 0\text{ V}$ , $V_{GS} = \pm 20\text{ V}$	-	-	$\pm 10$	$\mu\text{A}$
$V_{GS(th)}$	Gate threshold voltage	$V_{DS} = V_{GS}$ , $I_D = 100\text{ }\mu\text{A}$	3	4	5	V
$R_{DS(on)}$	Static drain-source on-resistance	$V_{GS} = 10\text{ V}$ , $I_D = 7\text{ A}$	-	700	900	m $\Omega$

1. Specified by design, not tested in production.

**Table 5. Dynamic**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$C_{iss}$	Input capacitance	$V_{DS} = 100\text{ V}$ , $f = 1\text{ MHz}$ , $V_{GS} = 0\text{ V}$	-	3145	-	pF
$C_{oss}$	Output capacitance		-	172	-	pF
$C_{rss}$	Reverse transfer capacitance		-	1	-	pF
$C_{o(tr)}^{(1)}$	Equivalent output capacitance time related	$V_{DS} = 0\text{ to }1200\text{ V}$ , $V_{GS} = 0\text{ V}$	-	161	-	pF
$C_{o(er)}^{(2)}$	Equivalent output capacitance energy related		-	65	-	pF
$R_g$	Intrinsic gate resistance	$f = 1\text{ MHz}$ , $I_D = 0\text{ A}$	-	2.4	-	$\Omega$
$Q_g$	Total gate charge	$V_{DD} = 1200\text{ V}$ , $I_D = 14\text{ A}$ , $V_{GS} = 0\text{ to }10\text{ V}$ (see the Figure 14. Test circuit for gate charge behavior)	-	89	-	nC
$Q_{gs}$	Gate-source charge		-	16	-	nC
$Q_{gd}$	Gate-drain charge		-	59	-	nC

1.  $C_{o(tr)}$  is a constant capacitance value that gives the same charging time as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 80%  $V_{DSS}$ .

2.  $C_{o(er)}$  is a constant capacitance value that gives the same stored energy as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 80%  $V_{DSS}$ .

**Table 6. Switching times**







Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 750\text{ V}$ , $I_D = 7\text{ A}$ , $R_G = 4.7\text{ }\Omega$ , $V_{GS} = 10\text{ V}$	-	34	-	ns
$t_r$	Rise time		-	14	-	ns
$t_{d(off)}$	Turn-off delay time	(see the Figure 13. Test circuit for resistive load switching times and Figure 18. Switching time waveform)	-	134	-	ns
$t_f$	Fall time		-	26	-	ns

**Table 7. Source-drain diode**


Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$I_{SD}$	Source-drain current		-	-	14	A
$I_{SDM}^{(1)}$	Source-drain current (pulsed)		-	-	56	A
$V_{SD}^{(2)}$	Forward on voltage	$V_{GS} = 0\text{ V}$ , $I_{SD} = 14\text{ A}$	-	-	1.5	V
$t_{rr}$	Reverse recovery time	$I_{SD} = 14\text{ A}$ , $di/dt = 100\text{ A}/\mu\text{s}$ , $V_{DD} = 60\text{ V}$	-	448	-	ns
$Q_{rr}$	Reverse recovery charge		-	8.24	-	$\mu\text{C}$
$I_{RRM}$	Reverse recovery current	(see the Figure 15. Test circuit for inductive load switching and diode recovery times)	-	36.8	-	A
$t_{rr}$	Reverse recovery time	$I_{SD} = 14\text{ A}$ , $di/dt = 100\text{ A}/\mu\text{s}$ , $V_{DD} = 60\text{ V}$ , $T_J = 150\text{ }^\circ\text{C}$	-	564	-	ns
$Q_{rr}$	Reverse recovery charge		-	9.48	-	$\mu\text{C}$
$I_{RRM}$	Reverse recovery current	(see the Figure 15. Test circuit for inductive load switching and diode recovery times)	-	33.6	-	A

1. Pulse width is limited by safe operating area.
2. Pulse test: pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5%.


## 2.1 Electrical characteristics (curves)

**Figure 1. Safe operating area**

**Figure 2. Normalized transient thermal impedance**

**Figure 3. Typical output characteristics**

**Figure 4. Typical transfer characteristics**

**Figure 5. Typical gate charge characteristics**

**Figure 6. Typical drain-source on-resistance**



**Figure 7. Typical capacitance characteristics**




**Figure 8. Normalized gate threshold vs temperature**




**Figure 9. Normalized on-resistance vs temperature**




**Figure 10. Normalized breakdown voltage vs temperature**




**Figure 11. Maximum avalanche energy vs temperature**




**Figure 12. Typical reverse diode forward characteristics**




### 3 Test circuits

**Figure 13. Test circuit for resistive load switching times**



AM01468v1

**Figure 14. Test circuit for gate charge behavior**



AM01469v1

**Figure 15. Test circuit for inductive load switching and diode recovery times**



AM01470v1

**Figure 16. Unclamped inductive load test circuit**


AM01471v1

**Figure 17. Unclamped inductive waveform**


AM01472v1

**Figure 18. Switching time waveform**



AM01473v1

## 4 Package information

To meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

### 4.1 TO-247 package information

Figure 19. TO-247 package outline



0075325\_11



**Table 8. TO-247 package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	4.85		5.15
A1	2.20		2.60
A2		1.27	
b	1.0		1.40
b1	2.0		2.40
b2	3.0		3.40
c	0.40		0.80
D	19.85		20.15
E	15.45		15.75
e	5.30	5.45	5.60
L	14.20		14.80
L1	3.70		4.30
L2		18.50	
ØP	3.55		3.65
ØR	4.50		5.50
S	5.30	5.50	5.70

## Revision history

**Table 9. Document revision history**

Date	Version	Changes
17-Oct-2013	1	First release.
19-Dec-2013	2	Datasheet promoted from preliminary to production data Modified: title and Features Minor text changes
20-Mar-2014	3	– Modified: note 3 in Table 2 – Modified: Qgs and Qgd typical values in Table 5 – Modified: typical values in Table 6 and 7 – Updated: Figure 6 – Minor text changes
11-Jan-2017	4	Updated title, features and description in cover page. Minor text changes in Section 1: "Electrical ratings" and Section 2: "Electrical characteristics". Changed Figure 7: "Static drain-source on-resistance".
19-Dec-2025	5	Updated <a href="#">Section 4.1: TO-247 package information</a> . Minor text changes.

## Contents

<b>1</b>	<b>Electrical ratings .....</b>	<b>2</b>
<b>2</b>	<b>Electrical characteristics.....</b>	<b>3</b>
2.1	Electrical characteristics (curves) .....	5
<b>3</b>	<b>Test circuits .....</b>	<b>7</b>
<b>4</b>	<b>Package information.....</b>	<b>8</b>
4.1	TO-247 package information .....	8
	<b>Revision history .....</b>	<b>10</b>

**IMPORTANT NOTICE – READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice.

In the event of any conflict between the provisions of this document and the provisions of any contractual arrangement in force between the purchasers and ST, the provisions of such contractual arrangement shall prevail.

The purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgment.

The purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of the purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

If the purchasers identify an ST product that meets their functional and performance requirements but that is not designated for the purchasers' market segment, the purchasers shall contact ST for more information.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to [www.st.com/trademarks](http://www.st.com/trademarks). All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2025 STMicroelectronics – All rights reserved