



Material Composition Declaration

© Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.

This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.

Adobe Reader version 7.0.5 is required to complete this declaration.

1752-2 1.1	IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x	Form Type * Distribute	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informat
------------	--	---------------------------	--

Supplier Information

Company Name * STMicroelectronics	Company Unique ID	Unique ID Authority	Response Date * N/A	Response Document ID				
Contact Name *	Title - Contact	Phone - Contact *	Email - Contact *					
Authorized Representative * GIUSEPPE VITALI PALMA	Title - Representative APM MD CHAMPION	Phone - Representative * N/A	Email - Representative * N/A	Supplier Comments or URL for Additional Information				
Requester Item Number	Mfr Item Number	Mfr Item Name	Effective Date	Version	Manufacturing Site	Weight *	UOM	Unit Type
	L6932D1.8TR	A5O7*UD26CA6	2011-11-16	A	MU1A	76.29	mg	Each
Alternate Recommendation	PACKAGE: SO 08 .15 JEDEC			Alternate Item Comments	ECOPACK1/ROHS; BSA: CD00206614			

Manufacturing Process Information

Terminal Plating / Grid Array Material Nickel/Palladium/Gold (Ni/Pd/Au)	Terminal Base Alloy CU Alloy	J-STD-020 MSL Rating 3	Peak Process Body Temperature 260 C	Max Time at Peak Temperature 30 seconds	Number of Reflow Cycles 3
--	---------------------------------	---------------------------	--	--	------------------------------

Comments

Disclaimer: While STMicroelectronics has endeavored to provide information which is accurate and up to date, this document and its contents are provided on a strict 'as is' and

Save the fields in this form to a file

Export Data

Import fields from a file into this form

Import Data

Locked

RoHS Material Composition Declaration

Declaration Type *

Simplified

RoHS Directive 2002/95/EC **RoHS Definition:** Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium

Supplier certifies that it gathered the information it provides in this form concerning RoHS restrictive substances using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form.

RoHS Declaration *

1 - Item(s) does not contain RoHS restricted substances per the definition above

Supplier Acceptance *

Accepted

Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.

Declaration Signature

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

	Item/SubItem Name	Homogeneous Material	Weight	Unit of Measure	Level	Substance Category	Substance	CAS	Exempt	Weight	Unit of Measure	Tolerance		PPM
												-	+	
	A507*UD26CA6	Silicon die	4.51	mg	Supplier	Silicon die	Silicon (Si)	7440-21-3		4.453	mg			987,36
					Supplier	die metallization	Aluminium (Al)	7429-90-5		0.002	mg			443
							Chromium (Cr)	7440-47-3		0.003	mg			665
							Nickel (Ni)	7440-02-0		0.023	mg			5,100
					Supplier	Die coating	Gamma-butyrolactone	96-48-0		0.019	mg			4,213
							Polyhydroxyamide	55295-98-2		0.009	mg			1,996
							Alcoxysilane	Proprietary		0.001	mg			222
	Leadframe	29.986	mg	supplier	frame alloy	Copper (Cu)	7440-50-8		29.713	mg				990,89
							Iron (Fe)	7439-89-6		0.014	mg			467
							Iron Phosphide (FeP)	26508-33-8		0.025	mg			834
					supplier	frame coating	Nickel (Ni)	7440-02-0		0.214	mg	0		7,137
							Palladium (Pd)	7440-05-3		0.014	mg			467
							Gold (Au)	7440-57-5		0.006	mg			200
	Die Attach	0.778	mg	supplier	glue	Silver (Ag)	7440-22-4		0.584	mg				750,64
							Epoxy Cresol Novolak	29690-82-2		0.191	mg			245,50
							1-isopropyl-2,2-dimethyl	6846-50-0		0.003	mg			3,856
	Bonding wire	0.162	mg	Supplier	Bonding wire	Gold (Au)	7440-57-5		0.162	mg				1,000,0
	Encapsulation	40.854	mg	supplier	Moulding Compound	Epoxy Cresol Novolak	29690-82-2		4.085	mg				99,990
							phenol resin	9003-35-4		1.634	mg			39,996
							Carbon Black	1333-86-4		0.409	mg			10,011
							Silica, vitreous	60676-86-0		33.5	mg			819,99
							Antimony Trioxide	1309-64-4		0.817	mg			19,998
					JIG I	Brominated Flame Ret	Brominated epoxy resin	68928-70-1		0.409	mg			10,011