



# Material Composition Declaration

© Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.

This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.

Adobe Reader version 7.0.5 is required to complete this declaration.

1752-2 1.1	IPC Web Site for Information on IPC-1752 Standard <a href="http://www.ipc.org/IPC-175x">http://www.ipc.org/IPC-175x</a>	Form Type * Distribute	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informat
------------	--	---------------------------	--

## Supplier Information

Company Name * STMicroelectronics	Company Unique ID	Unique ID Authority	Response Date *	Response Document ID				
Contact Name *	Title - Contact	Phone - Contact *	Email - Contact *	Duplicate Contact -> Authorized Representative				
Authorized Representative * Emilio Castelli	Title - Representative APG Material Declaration Cham	Phone - Representative *	Email - Representative *	Supplier Comments or URL for Additional Information				
Requester Item Number	Mfr Item Number	Mfr Item Name	Effective Date	Version	Manufacturing Site	Weight *	UOM	Unit Type
	TDA7540B	D51S*A124BC6	2010-02-12	A	MU1A	716.95	mg	Each
Alternate Recommendation	LQFP 80 14x14x1.4 1			Alternate Item Comments	Internal ST reference: BSA: CD00208894 EcoPack2			

## Manufacturing Process Information

Terminal Plating / Grid Array Material	Terminal Base Alloy	J-STD-020 MSL Rating	Peak Process Body Temperature	Max Time at Peak Temperature	Number of Reflow Cycles
Tin (Sn)	CU Alloy	3	260 C	30 seconds	3

Comments

**Disclaimer: While STMicroelectronics has endeavored to provide information which is accurate and up to date, this document and its contents are provided on a strict 'as is' and**

Save the fields in this form to a file

Export Data

Import fields from a file into this form

Import Data

Clear all of the fields on this form

Reset Form

Lock the fields on this form to prevent changes

Lock Supplier Fields

## RoHS Material Composition Declaration

Declaration Type \*

Simplified

RoHS Directive  
2002/95/EC

**RoHS Definition:** Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium

Supplier certifies that it gathered the information it provides in this form concerning RoHS restrictive substances using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form.

RoHS Declaration \*

1 - Item(s) does not contain RoHS restricted substances per the definition above

Supplier Acceptance \*

Accepted

**Exemptions:** If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.

## Declaration Signature

**Instructions:** Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

## Homogeneous Material Composition Declaration for Electronic Products

**SubItem Instructions:** The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

**Substance Instructions:** [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

**Line Functions:** +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

		Item/SubItem Name			Homogeneous Material	Weight	Unit of Measure			Level	Substance Category			Substance	CAS	Exempt	Weight	Unit of Measure	Tolerance		PPM
+I	-I		+M	-M				+C	-C			+S	-S						-	+	
+I	-I	LQFP 80 14x14x1.4	+M	-M	Integrated circuit	18.659	mg	+C	-C	Supplier	Silicon die	+S	-S	Silicon (Si)	7440-21-3		18.655	mg			999,78
								+C	-C		die metallization	+S	-S	Aluminium (Al)	7429-90-5		0.001	mg			54
								+C	-C		die metallization	+S	-S	Copper (Cu)	7440-50-8		0.003	mg			161
			+M	-M	Leadframe	193.72	mg	+C	-C	supplier	frame alloy	+S	-S	Copper (Cu)	7440-50-8		182.9	mg			944,14
								+C	-C		frame alloy	+S	-S	Nickel (Ni)	7440-02-0		5.704	mg			29,445
								+C	-C		frame alloy	+S	-S	Silicium (Si)	7440-21-3		1.236	mg			6,380
								+C	-C		frame alloy	+S	-S	Magnesium (Mg)	7439-95-4		0.285	mg			1,471
								+C	-C		frame coating	+S	-S	Silver (Ag)	7440-22-4		3.595	mg			18,558
			+M	-M	Die Attach	2.39	mg	+C	-C	supplier	glue	+S	-S	Isobornyl Methacrylate	7534-94-3		0.131	mg			54,812
								+C	-C		glue	+S	-S	Bismaleimide resin	na		0.096	mg			40,167
								+C	-C		glue	+S	-S	Silver (Ag)	7440-22-4		2.163	mg			905,02
			+M	-M	Bonding wire	1.703	mg	+C	-C	Supplier	Bonding wire	+S	-S	Gold (Au)	7440-57-5		1.703	mg			1,000,0
			+M	-M	Encapsulation	492.016	mg	+C	-C	supplier	Moulding Compound	+S	-S	Solid Epoxy Resin	na		39.361	mg			79,999
								+C	-C		Moulding Compound	+S	-S	Phenol Resin	na		19.681	mg			40,001
								+C	-C		Moulding Compound	+S	-S	Silica, vitreous	60676-86-0		428.546	mg			871,00
								+C	-C		Moulding Compound	+S	-S	Carbon-black	1333-86-4		2.46	mg			5,000
								+C	-C	B	Bismuth/Bismuth Com	+S	-S	Bismuth (Bi)	7440-69-9		1.968	mg			4,000
			+M	-M	Finishing	8.462	mg	+C	-C	supplier	connection coating	+S	-S	Tin (Sn)	7440-31-5		8.462	mg			1,000,0