



Silicon carbide Power MOSFET 1200 V, 21 mΩ typ., 91 A in an HiP247 long leads package



HiP247 long leads



Features

Order code	V _{DS}	R _{DS(on)} typ.	I _D
SCTWA70N120G2V	1200 V	21 mΩ	91 A

- Very fast and robust intrinsic body diode
- Extremely low gate charge and input capacitance
- Very high operating junction temperature capability (T_J = 200 °C)

Applications

- Switching mode power supply
- DC-DC converters
- Industrial motor control

Description

This silicon carbide Power MOSFET device has been developed using ST's advanced and innovative 2nd generation SiC MOSFET technology. The device features remarkably low on-resistance per unit area and very good switching performance. The variation of switching loss is almost independent of junction temperature.



Product status link	
SCTWA70N120G2V	
Product summary	
Order code	SCTWA70N120G2V
Marking	SCT70N120G2
Package	HiP247 long leads
Packing	Tube

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	1200	V
V_{GS}	Gate-source voltage	-10 to 22	V
	Gate-source voltage (recommended operating values)	-5 to 18	
I_D	Drain current (continuous) at $T_C = 25^\circ\text{C}$	91	A
	Drain current (continuous) at $T_C = 100^\circ\text{C}$	69	
$I_{DM}^{(1)}$	Drain current (pulsed)	274	A
P_{TOT}	Total power dissipation at $T_C = 25^\circ\text{C}$	547	W
T_{stg}	Storage temperature range	-55 to 200	$^\circ\text{C}$
T_J	Operating junction temperature range		

1. Pulse width is limited by safe operating area.

Table 2. Thermal data

Symbol	Parameter	Value	Unit
R_{thJC}	Thermal resistance, junction-to-case	0.32	$^\circ\text{C}/\text{W}$
R_{thJA}	Thermal resistance, junction-to-ambient	40	$^\circ\text{C}/\text{W}$

2 Electrical characteristics

($T_C = 25^\circ\text{C}$ unless otherwise specified).

Table 3. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(\text{BR})\text{DSS}}$	Drain-source breakdown voltage	$V_{GS} = 0 \text{ V}, I_D = 1 \text{ mA}$	1200			V
I_{DSS}	Zero-gate voltage drain current	$V_{DS} = 1200 \text{ V}, V_{GS} = 0 \text{ V}$			10	μA
I_{GSS}	Gate-body leakage current	$V_{DS} = 0 \text{ V}, V_{GS} = -10 \text{ to } 22 \text{ V}$			± 100	nA
$V_{GS(\text{th})}$	Gate threshold voltage	$V_{DS} = V_{GS}, I_D = 1 \text{ mA}$	1.9	2.45	4.9	V
$R_{\text{DS(on)}}$	Static drain-source on-resistance	$V_{GS} = 18 \text{ V}, I_D = 50 \text{ A}$		21	30	$\text{m}\Omega$
		$V_{GS} = 18 \text{ V}, I_D = 50 \text{ A}, T_J = 200^\circ\text{C}$		46		

Table 4. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	$V_{DS} = 800 \text{ V}, f = 1 \text{ MHz}, V_{GS} = 0 \text{ V}$	-	3540	-	pF
C_{oss}	Output capacitance		-	176	-	pF
C_{rss}	Reverse transfer capacitance		-	28	-	pF
R_G	Intrinsic gate resistance	$f = 1 \text{ MHz}, I_D = 0 \text{ A}$	-	1	-	Ω
Q_g	Total gate charge	$V_{DD} = 800 \text{ V}, I_D = 50 \text{ A}, V_{GS} = -5 \text{ to } 18 \text{ V}$	-	150	-	nC
Q_{gs}	Gate-source charge		-	28	-	nC
Q_{gd}	Gate-drain charge		-	63	-	nC

Table 5. Switching energy

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
E_{on}	Turn-on switching energy	$V_{DD} = 800 \text{ V}, I_D = 50 \text{ A}$	-	1019	-	μJ
E_{off}	Turn-off switching energy	$R_G = 3.3 \Omega, V_{GS} = -5 \text{ to } 18 \text{ V}$	-	378	-	μJ

Table 6. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(\text{on})}$	Turn-on delay time	$V_{DD} = 800 \text{ V}, I_D = 50 \text{ A}$	-	16	-	ns
t_r	Rise time		-	9.5	-	ns
$t_{d(\text{off})}$	Turn-off delay time		-	37	-	ns
t_f	Fall time		-	22	-	ns

Table 7. Reverse SiC diode characteristics

Symbol	Parameter	Test conditions	Min	Typ.	Max	Unit
V _{SD}	Forward on voltage	I _{SD} = 50 A, V _{GS} = 0 V	-	2.7	-	V
t _{rr}	Reverse recovery time	I _{SD} = 50 A, V _{DD} = 800 V,	-	11.16	-	ns
Q _{rr}	Reverse recovery charge	V _{GS} = -5 to 18 V	-	276	-	nC
I _{RRM}	Reverse recovery current		-	40	-	A

2.1 Electrical characteristics (curves)







Figure 1. Safe operating area

Figure 2. Maximum transient thermal impedance

Figure 3. Typical output characteristics ($T_J = 25^\circ C$)

Figure 4. Typical output characteristics ($T_J = 200^\circ C$)

Figure 5. Typical transfer characteristics

Figure 6. Total power dissipation












Figure 7. Typical gate charge characteristics

Figure 8. Typical capacitance characteristics

Figure 9. Typical switching energy vs drain current

Figure 10. Typical switching energy vs temperature

Figure 11. Normalized breakdown voltage vs temperature

Figure 12. Normalized gate threshold vs temperature



Figure 13. Normalized on-resistance vs temperature

Figure 14. Typical reverse conduction characteristics ($T_J = 25^\circ\text{C}$)

Figure 15. Typical reverse conduction characteristics ($T_J = 200^\circ\text{C}$)

Figure 16. Typical switching energy vs gate resistance


3 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

3.1 HiP247 long leads package information

Figure 17. HiP247 long leads package outline



BACK VIEW

Table 8. HiP247 long leads package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.90	5.00	5.10
A1	2.31	2.41	2.51
A2	1.90	2.00	2.10
b	1.16		1.26
b2			3.25
b3			2.25
c	0.59		0.66
D	20.90	21.00	21.10
E	15.70	15.80	15.90
E2	4.90	5.00	5.10
E3	2.40	2.50	2.60
e	5.34	5.44	5.54
L	19.80	19.92	20.10
L1			4.30
P	3.50	3.60	3.70
Q	5.60		6.00
S	6.05	6.15	6.25
aaa		0.04	0.10

Revision history

Table 9. Document revision history

Date	Revision	Changes
10-Oct-2022	1	First release.

Contents

1	Electrical ratings	2
2	Electrical characteristics.....	3
2.1	Electrical characteristics (curves)	5
3	Package information.....	8
3.1	HiP247 long leads package information.....	8
	Revision history	10

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2022 STMicroelectronics – All rights reserved